

Table Top Low Speed Centrifuge **TL220**



TL220 is powerful versatile and indispensable centrifuge for routine laboratories. It is not only ideal for small laboratory; it can be also very useful in medium and large laboratories. It is high performance motor, **Maintenance free, Brushless** and **Microprocessor** controller for preselecting of speed and time.

- Easy entry of key pad
- Easy to read, digital display
- Display of correct speed & time valume
- Impulse key for short centrifuge
- Running time in minute, max 99 min
- Open lid key
- Lid locking
- Emergency lid lock release
- Motor over heating protection

- Max capacity: 24 x 10 ml
- Max speed: 4000 r/min
- Max ref: 2220 x g



MODEL	TL220						
Rotors	Angle 	Angle 	Angle 	Swing 			
Cat No.	AM 1810		AM 2410		AM 1220		SM 0815
Picture bucket							
Cat NO.	P10			P20		M15	
Tube per rotor	18		24		12		8
Capacity in ml	15 ml		10 ml		20ml		15 ml
ØXL in mm	15x96	16x85	17x110		21x99		16.5x120 17.5x99
Picture tube							
Max Speed	4000r/min						
Max RCF	2220xg						
Timer Range	0~99min						
Power Supply	AC220V50Hz5A						
Dimensions(LxWxH)	330x420x275mm						
Weight	15kg						